


KIT exterior IP, 3MP

	Mini Bullet Camera, 3Mpx, IR 20~30m
Model	DS-2CD2032-I
Camera	
Image sensor	1/3" Progressive scan CMOS
Min. illumination	0.07 Lux @ F1.2, AGC ON, 0 Lux with IR
Shutter speed	1/25s ~ 1/100.000s
Lens	4mm, or 6mm, or 12mm
Lens mount	M12
Day & Night	IR cut filter with auto switch
Wide dynamic range	Digital WDR
Digital noise reduction	3D DNR
Compression standard	
Video compression	H.264
Video bit rate	32 Kbps ~ 16 Mbps
Dual stream	Yes
Image	
Max. resolution	2048 x 1536
Frame rate	12.5fps: 2048x1536, 25fps: 1920x1080, 25fps: 1280x720
Image settings	Saturation, Brightness, Contrast adjustable by client software or web browser
BLC	Yes, zone configurable
Network	
Network storage	NAS
Alarm trigger	Motion detection, Dynamic analysis, Tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, UPnP, ICMP, IGMP, SNMP, FTP, 802.1x, QoS, HTTPS (SIP, SRTP, IPv6 optional)
Security	User authentication, Watermark
Standard	ONVIF, PSIA, CGI
Interface	
Communication interface	1 RJ45 10M/100M ethernet interface
Reset button	Yes
General	
Operating conditions	-30°C ~ +60°C Humidity 95% or less (non-condensing)
Power supply	DC 12V PoE (802.3af)
Power consumption	5W; max. 7W with IR cut filter ON
Ingress protection level	IP66
IR range	approx. 20 to 30 meters
Dimensions	60.4 x 76.9 x 139.28mm

Tel/fax 021.252.09.43;

Mobil: 0765.449.127;

www.instalarecamere.ro







NVR 4 Ch IP 6Mpx, 1 IN/OUT audio, HDMI

Model		DS-7604NI-E1/A
Video / Audio input		
IP video input		4-ch
Two-way audio input		1-ch, RCA, 2.0Vp-p, 1K Ω
Network incoming bandwidth		40Mbps
Output bandwidth		80Mbps
Remote connection		128
Video / Audio output		
Recording resolution		6MP / 5MP / 3MP / 1080P / UXGA / 720p / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
HDMI / VGA output	1-ch, resolution:	1920x1080P/60Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Audio output		1-ch, RCA, Linear, 1K Ω
Playback resolution		6MP / 5MP / 3MP / 1080P / UXGA / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
Synchronous playback		4-ch 720P or 2-ch 1080P or 1-ch 5MP
Hard disk		
SATA		1 SATA interfaces
Capacity		Up to 4Tb for each disk
External interface		
Network interface		1 RJ-45 10/100/1000 Mbps self-adaptive ethernet interface
Serial interface		1 RS-485 half-duplex interface
USB interface		2 x USB 2.0
Others		
Power supply		12V DC
Consumption		\leq 10W (without hard disk)
Working temperature		-10 $^{\circ}$ C ~ +55 $^{\circ}$ C
Working humidity		10% ~ 90%
Chassis		19-inch rack-mounted 1U chassis
Dimensions (W x D x H)		315 x 230 x 45mm
Weight		\leq 1Kg (without hard disk)

Tel/fax 021.252.09.43;

Mobil: 0765.449.127;

www.instalarecamere.ro

	<p>Hard disk Western Digital 1 TB SATA3 64MB IntelliPower RPM</p>
	<p>Cablu FTP cat 5e</p>
	<p>Sursa AC 100~240V, DC 12V/5A;</p>
	<p>Instalare camere de supraveghere si traseu de cablu. Configurare NVR in functie de cerintele beneficiarului. Configurare setari de retea pentru vizionare pe PC sau smartphone.</p>

Tel/fax 021.252.09.43;

Mobil: 0765.449.127;

www.instalarecamere.ro